

VIPOIL

FORM RELEASE AGENT

Low viscosity **VIPOIL** wax emulsion suitable for applying on wood, steel and plastic forms when manufacturing concrete constructions and on construction sites. Ensures lower mechanical resistance when removing forms from concrete constructions, ensures cleaner forms and makes their cleaning easier. Reduces air-bubble formation and does not leave stains on concrete surfaces. **Instructions for use.** Before applying the product on the forms, clean their surfaces from any residual concrete and other existing coatings. VIPOIL is applied as a thin coating by spraying it, applying it with a brush or a roller. It is recommended to apply the product on horizontal surfaces. Consumption depends on the material of the form and surface condition: 40 to 80 ml/m². Allow the coating to dry before performing other concrete works. Depending on the environment conditions and humidity, the drying time is from 20 to 40 minutes. The minimum working environment temperature is +5 °C Mix the product before use. Store in a closed container at a temperature from +5 °C to +30 °C. Protect from freezing. Shelf life: 2 years from the manufacturing date. Manufacturing date provided on the packaging. **H319 causes serious eye irritation. P102 Keep away from children. P280 Wear protective gloves and eye protection. P305 + P351 + P338 IF IN CONTACT WITH EYES: Rinse carefully with water for several minutes. Remove contact lenses if you have them on and it can be done easily. Continue to rinse. P337 + P313 If the eye irritation persists: seek medical advice.**

Attention

